

GRADE 80 CHAIN SLING

SPECIFICATION FOR GRADE 80 CHAIN SLING - 10mm - 2 LEG - CLEVIS

**AS
3775.1**

Certified

**Proof
Tested
x2_{WLL}**

**Safety Factor
4-1**

**G80
Alloy Steel**



Grade 80 Chain Sling - 10mm 2 leg - Clevis Type Grab Shortener & Clevis Self Locking Hook

Every Austlift G80 chain sling is fabricated using high quality Grade 80 chain and components.

Each sling is proof tested, individually serial numbered, tagged and complete with test certificates.

Manufactured to the specifications of Austlift and according to Australian Standard AS 3775.1.

Application

- Building construction sites
- Ship building yards
- Factory production workshops
- Mine production sites
- Engineering workshops

Features

- Each sling is proof tested 2 x WLL.
- Individually serial numbered.
- Supplied with individual test certificate and stainless steel safety tag.
- Plastic bucket & lid provided with the sling kit
- Complies to AS 3775.1-2004
- Break Load Limit is 4 x the load indicated



WORKING LOAD LIMIT (t) - GRADE 80 (T)

Chain	Slings of 2, 3 or 4 legs				2 leg slings
					
Chain size	Straight sling			Reeved sling Max 60°	Basket sling Max 60°
mm	60°	90°	120°		
10	5.5	4.5	3.2	4.1	7.2



Full Member

SIZE (mm)	CODE	SLING LENGTH	Wt. (kg)	DIRECT LOAD			SHORTENING HOOK	END FITTING
				60°	90°	120°		
10mm	951021	1M	9.16	5.5T	4.5T	3.2T	GC-10-8	LC-10-8
	951022	2M	13.58	5.5T	4.5T	3.2T	GC-10-8	LC-10-8
	951023	3M	18.00	5.5T	4.5T	3.2T	GC-10-8	LC-10-8
	951024	4M	22.42	5.5T	4.5T	3.2T	GC-10-8	LC-10-8
	951025	5M	26.84	5.5T	4.5T	3.2T	GC-10-8	LC-10-8
	951026	6M	31.26	5.5T	4.5T	3.2T	GC-10-8	LC-10-8

NSW Head Office
 43 Frank Street
 Wetherill Park, NSW 2164
 02 9757 2277

WA Office
 42 Mulgool Road
 Malaga, WA 6090
 08 9248 6674

QLD Office
 7 Durbell Street
 Acacia Ridge, QLD 4110
 07 3272 0777

VIC Office
 47 Technology Drive
 Sunshine West, VIC 3020
 03 9314 5525